HEATLOK SOY®



GREEN SOLUTION — ONE APPLICATION

Our unique formula incorporates 14% of recycled plastic and renewable oils to create our high-performing, closed-cell polyurethane spray foam insulation. A single application saves time and money in construction costs.

R-value = 7.4 @ 1 inch
Density = 2 lb/ft³
Contains 14% Renewable and Recycled Content



FIVE BENEFITS WITH ONE APPLICATION

Heatlok Soy® — our high-performing, versatile spray foam insulation for commercial and residential construction creates a specialized engineered building envelope, which provides better thermal resistance, an excellent air barrier, and a recognized vapor retarder. Demilec continues to strive toward innovative, scientific advancements in high-efficiency spray foam insulation solutions, elastomeric coatings, high-performance quality products, and superior service.

- Air barrier
- Insulation
- Water-resistive barrier
- Vapor barrier
- Drain plane





© 2015 Demilec. Partial or total reproduction of any information, graphics, or statements in this product sheet without prior written consent is unauthorized. This product sheet is intended for general guidance and information only. No guarantee or warranty is intended or implied. Detailed information about our products, systems, installers, and services is available from a representative in your area. For a list of representatives, visit www.Demilec.com, or call 1.877.Demilec (1.877.336.4532), or 817.640.4900.